

Specifications

1. Photos







2. Y83-250Z Automatic Briquetting Press technical parameters

| Sr. | Content | | | | |
|-----|-----------------------------------|--------------------|--|------------------------|---------|
| 1 | M. Cyl. | Model | YG320/200-355 | Stroke | 355 mm |
| | | Nominal Force | 2000kN | Qty | 1 pc |
| 2 | Auxiliary Cyl. | Model | YG100/70-360 | Stroke | 360mm |
| | | Nominal Force | 500kN | Qty | 1 pc |
| 3 | Discharging Cyl. | Model | YG110/63-160 | Stroke | 160mm |
| | | Nominal Force | 250kN | Qty | 1 pc |
| 4 | Hydraulic Pump | Type | 80YCY14-1B | Max Operating Pressure | 31.5MPa |
| | | Rated Displacement | 80ml/r | Qty | 1pc |
| 5 | Motor | Type | Y180M-4 | Rated Power | 18.5kW |
| | | Rated Speed | 1470rpm | Qty | 1 pc |
| 6 | A single working cycle time | | < 10~12 S | | |
| 7 | Cavity size | | Φ80×180mm 或 Φ100×180mm | | |
| 8 | Hydraulic system Working pressure | | 25MPa | | |
| 9 | power supply | | 380V/3PH, 50Hz | | |
| 10 | hydraulic oil specification | | ISO 68 & ISO 46 | | |
| 11 | The production efficiency | | 1-1.5tons/hour(In view of the cast iron) | | |
| 12 | Capacity of hydraulic chamber | | 1500 L | | |
| 13 | total power of the device | | 18.5kW | | |
| 14 | Main machine size | | 1600×1000×3000 mm | | |
| 15 | Machine Weight | | Approx.6500kg | | |
| 16 | Operation System | | PLC Operation | | |

3. Y83-315Z Automatic Briquetting Press technical parameters

| Sr. | Content | | | | |
|-----|-----------------------------------|--------------------|--|------------------------|---------|
| 1 | M. Cyl. | Model | YG360/200-400 | Stroke | 400 mm |
| | | Nominal Force | 2650kN | Qty | 1 pc |
| 2 | Auxiliary Cyl. | Model | YG100/70-410 | Stroke | 410mm |
| | | Nominal Force | 500kN | Qty | 1 pc |
| 3 | Discharging Cyl. | Model | YG125/80-160 | Stroke | 160mm |
| | | Nominal Force | 250kN | Qty | 1 pc |
| 4 | Hydraulic Pump | Type | 80YCY14-1B | Max Operating Pressure | 31.5MPa |
| | | Rated Displacement | 80ml/r | Qty | 1pc |
| 5 | Motor | Type | Y180L-4 | Rated Power | 22kW |
| | | Rated Speed | 1470rpm | Qty | 1 pc |
| 6 | A single working cycle time | | < 10~12 S | | |
| 7 | Cavity size | | Φ100×180mm 或 Φ110×180mm | | |
| 8 | Hydraulic system Working pressure | | 25MPa | | |
| 9 | power supply | | 380V/3PH, 50Hz | | |
| 10 | hydraulic oil specification | | ISO 68 & ISO 46 | | |
| 11 | The production efficiency | | 1.2-2tons/hour(In view of the cast iron) | | |
| 12 | Capacity of hydraulic chamber | | 2500 L | | |
| 13 | total power of the device | | 22kW | | |
| 14 | Main machine size | | 2500×1200×3000 mm | | |
| 15 | Machine Weight | | Approx.8000kg | | |
| 16 | Operation System | | PLC Operation | | |

4.Note:

- A. This price for FOB SHANGHAI based.
- B. Delivery time:30 days
- C. Validity date:30 days
- D. Guarantee for quality:12 months
- E. Payment : 30% advance, 70% paid before shipment, T/T .
- F. The product has passed ISO9001-2000 international quality system certification and European Union CE authentication!

Contact: Mr Wilson Zhang

website: www.aupujx.com

email: wilson@aupujx.com

Skype: wilsonzzh

QQ:983365051

Mob:+86-13382283038

Tel:+86-510-86961170